

Product data sheet

TS 3000 EN3



Overhead door closer with guide rail for single leaf doors with
a leaf width up to 950 mm

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 950 mm leaf width
- Door leaf and transom installation on the hinge and opposite hinge side

PRODUCT FEATURES

- Fixed closing force of EN3
- Can be used for right and left hand doors without conversion
- Hydraulic latching action which accelerates the door shortly before it is closed
- All functions can be adjusted from the front

TECHNICAL DATA

Productname	TS 3000 EN3
Closing force in accordance with EN 1154	EN 3
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	950 mm
Leaf width (max.)	950 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side, Transom installation hinge side, Door leaf installation opposite hinge side
Opening angle (max.)	180 °
Suitability for fire protection doors	Yes
Closing force adjustable	No
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	No
Hold-open function	Optional
Smoke switch integrated	No

PART**GUIDE RAIL TS 5000 / 3000 VERTICALLY ADJUSTABLE ***

With height compensation +/- 2 mm and lever



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115191	silver-coloured	448.5 x 30.5 x 20.5 mm
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115192	according to RAL	448.5 x 30.5 x 20.5 mm

GUIDE RAIL BG TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm, with lever, opposite hinge side



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail BG TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115194	according to RAL	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115193	silver-coloured	448.5 x 30.5 x 20.5 mm

GUIDE RAIL TS 5000 / 3000

Standard guide rail with lever



Designation	Description	Ident-No.	Colour	Dimensions	Spindle extension
Guide rail TS 3/TS 5000	Standard, with lever	015695	white RAL 9016	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	000773	according to RAL	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	068221	silver-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/TS 5000	Standard, with lever	014945	Stainless steel optic	448.5 x 30.5 x 20.5 mm	

GUIDE RAIL BG TS 5000 / 3000

Standard guide rail with lever, opposite hinge side



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025655	silver-coloured	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025656	according to RAL	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029404	white RAL 9016	448.5 x 30.5 x 20.5 mm
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	028732	Stainless steel optic	448.5 x 30.5 x 20.5 mm

TS 3000 EN3



CLOSER BODY TS 3000 EN3 *

Main body for overhead door closer with guide rail EN3



Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 3000 EN3 Closer	Size EN 3 (without guide rail and lever)	102308	according to RAL	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN3 Closer	Size EN 3 (without guide rail and lever)	102247	silver-coloured	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN3 Closer	Size EN 3 (without guide rail and lever)	102306	dark bronze	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN3 Closer	Size EN 3 (without guide rail and lever)	102307	white RAL 9016	EN 3	226 x 46 x 60 mm

T-STOP GUIDE RAIL BG TS 3000 / 5000

With opening restrictor and lever, opposite hinge side



Designation	Description	Ident-No.	Colour	Dimensions
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102368	according to RAL	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102367	Stainless steel optic	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	108482	white RAL 9016	452.5 x 33 x 30 mm
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102366	silver-coloured	452.5 x 33 x 30 mm

T-STOP GUIDE RAIL TS 3000/ 5000

With opening restrictor and lever



Designation	Description	Ident-No.	Colour	Dimensions
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	108481	white RAL 9016	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102364	Stainless steel optic	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102365	according to RAL	452.5 x 33 x 30 mm
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102363	silver-coloured	452.5 x 33 x 30 mm

ACCESSORIES**COVER CAP DOOR CLOSER ***

For TS 3000/TS 2000, can only be used for door leaf installation



Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	072769	Stainless steel	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	072770	Brass	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	013487	silver-coloured	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	014855	white RAL 9016	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	014849	dark bronze	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	014856	according to RAL	237 x 55 x 67.2 mm

MECHANICAL HOLD-OPEN UNIT

For standard/T-Stop/Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Mechanical hold-open unit	for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on and off, can be overridden	071924

FLEXIBLE OPENING RESTRICTOR

for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Flexible opening restrictor	for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, curved shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092928	Polished stainless steel	277 x 54 x 72 mm
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092929	Satin stainless steel	277 x 54 x 72 mm

TS 3000 EN3



COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, rectangular shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092924	Satin stainless steel	237 x 54 x 72 mm
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092923	Polished stainless steel	237 x 54 x 72 mm

INSTALLATION MATERIAL

DRILLING TEMPLATE DOOR CLOSER

for TS 5000/TS 4000/TS 3000/TS 2000



Designation	Description	Ident-No.
Drilling template door closer	for TS 5000/TS 4000/TS 3000/TS 2000	053134

GLASS CLAMPING SHOE

For TS 3000 / 2000 NV



Designation	Description	Ident-No.	Colour	Glass thickness
Glass clamping shoe	for TS 3000/TS 2000 NV	014835	silver-coloured	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014843	white RAL 9016	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014836	dark bronze	10 mm
Glass clamping shoe	for TS 3000/TS 2000 NV	014845	according to RAL	10 mm

MOUNTING PLATE AND COUNTERPLATE ALL-GLASS DOOR

For TS 3000 / 2000 NV



Designation	Description	Ident-No.	Colour	Glass thickness
Mounting plate and counterplate all-glass door	for TS 3000/TS 2000 NV	090259	silver-coloured	10 mm

MOUNTING PLATE GUIDE RAIL BG

For standard, EClime, T-Stop and EFS guide rail, opposite hinge side



Designation	Description	Ident-No.	Colour
Mounting plate guide rail BG	for standard / EClime / T-Stop / EFS guide rail	124684	according to RAL
Mounting plate guide rail BG	for standard / EClime / T-Stop / EFS guide rail	124683	silver-coloured

MOUNTING PLATE GUIDE RAIL

For standard, EClime, T-Stop and EFS guide rail



Designation	Description	Ident-No.	Colour
Mounting plate guide rail	for standard / EClime / T-Stop / EFS guide rail	001512	silver-coloured
Mounting plate guide rail	for standard / EClime / T-Stop / EFS guide rail	104515	according to RAL
Mounting plate guide rail	for standard / EClime / T-Stop / EFS guide rail	129252	white RAL 9016

MOUNTING PLATE DOOR CLOSER

for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1



Designation	Description	Ident-No.	Colour	Dimensions
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011232	dark bronze	226 x 60 x 5 mm
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011233	white RAL 9016	226 x 60 x 5 mm
Mounting plate door closer *	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	135237	black RAL 9005	226 x 60 x 5 mm
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011230	silver-coloured	226 x 60 x 5 mm
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011234	according to RAL	226 x 60 x 5 mm

LINTEL CASING BRACKET

for standard guide rail



Designation	Description	Ident-No.	Colour
Lintel casing bracket	for standard guide rail	030033	dark bronze
Lintel casing bracket	for standard guide rail	028393	Stainless steel optic
Lintel casing bracket	for standard guide rail	025657	silver-coloured
Lintel casing bracket	for standard guide rail	025658	according to RAL
Lintel casing bracket	for standard guide rail	030034	white RAL 9016

LINTEL CASING BRACKET

For ECLine and T-Stop guide rail



TS 3000 EN3

Designation	Description	Ident-No.	Colour
Lintel casing bracket	For ECLine and T-Stop guide rail	115006	silver-coloured
Lintel casing bracket	For ECLine and T-Stop guide rail	115007	according to RAL

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.