

Product data sheet Perlan 140 set for timber leaves



Sliding door fitting for ceiling installation and timber leaf

AREAS OF APPLICATION

- ightarrow For ceiling and wall mounting
- ightarrow For leaf weights up to 80 kg

Product data sheet | Page 2 of 4 Perlan 140 set for timber leaves



PRODUCT FEATURES

ightarrow Sliding door fitting for ceiling installation and timber leaf with up to 80 kg leaf weight

TECHNICAL DATA

Productname	Perlan 140 set for timber leaves		
Leaf weight (max.)	80 kg		
Corrosion protection class	2		
Colour	EV1		

VARIANTS / ORDER INFO

Designation	Description	ldent- No.	Colour	Leaf width (min.)	Leaf width (max.)
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one- sided, for track 2450 mm two-sided.	134888	EV1	860 mm	1240 mm
Perlan 140 set for timber leaves	For ceiling installation with standard suspension plate and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one- sided, for track 2450 mm two-sided.	134887	EV1	535 mm	1000 mm

PART

FLOOR GUIDE FOR WOODEN LEAF

Floor guide for wooden leaves mounted on the floor



Designation	Description	Ident-No.	Colour
Floor guide for timber leaf standard	Without attachment material	002191	Galvanised



END STOP PERLAN 140 (ALSO KS)

End stop for sliding leaves also suitable for outdoor use



Designation	Description	Ident-No.
End stop Perlan 140 (also KS)	Steel parts made of stainless steel	119362

END CAP PERLAN TRACK

End cap Perlan track



Designation	Ident-No.	Colour
End cap Perlan track	119649	black

PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm

()()) ()())

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, short, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128876	575 mm	900 mm

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com 2024-04-24T02:49:18Z

TRACK PERLAN 140

Track for sliding door fitting

with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
with countersunk drill holes (prepared for Perlan SoftStop)	135061	Stainless steel optic
with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	135050	Stainless steel optic
with countersunk drill holes (prepared for Perlan SoftStop)	135049	Stainless steel optic
with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1
	with countersunk drill holes (prepared for Perlan SoftStop) with countersunk drill holes (prepared for Perlan SoftStop)	with countersunk drill holes (prepared for Perlan SoftStop)128660with countersunk drill holes (prepared for Perlan SoftStop)128662with countersunk drill holes (prepared for Perlan SoftStop)135061with countersunk drill holes (prepared for Perlan SoftStop)135048with countersunk drill holes (prepared for Perlan SoftStop)135050with countersunk drill holes (prepared for Perlan SoftStop)135049with countersunk drill holes (prepared for Perlan SoftStop)135049with countersunk drill holes (prepared for Perlan SoftStop)135047with countersunk drill holes (prepared for Perlan SoftStop)142519



